GOLF CART DC BATTERIES


DSAM GC 110



MECHANICAL SPECIFICATIONS


Group Size	GC2
Terminal Type	Special Marine
L x W x H x TH [in]	10.3 x 7.1 x 9.6 x 10.8 in
L x W x H x TH [mm]	261 x 181 x 245 x 274 mm
Weight [lbs / kg]	58.64 lbs / 26.6 kg
Case Material	Polypropylene
Cover	Polypropylene
Handle	Polypropylene
Hold Down	B00
Cell Layout	5


BATTERY DIAGRAMS



Terminal Type: Marine Dual

Hold Down: B00





ELECTRICAL SPECIFICATIONS

Voltage (V)	6V
Reserve Capacity (RC) @25A	110 min
C20 (Ah)	230
C05 (Ah)	190
Internal Resistance (mΩ)	3.35 mΩ

CHARGE DISCHARGE AND TEMPERATURE

Self-Discharge/Month 68°F (20°C)	2.9%
Self-Discharge/Month 104°F (40°C)	5.6%
Operating Temperature (Range)	-4°F/-20°C to 122°F/50°C
Storage Temperature (Range)	-4°F/-20°C to 104°F/40°C

CHARGE VOLTAGES

CHARGE STAGE	6V	12V	18V	24V
Bulk	7.2V-7.35V	14.4V-14.7V	21.6V-22.05V	28.8V to 29.4V
Absorption	7.2V-7.35V	14.4V-14.7V	21.6V-22.05V	28.8V to 29.4V
Float	6.69V-6.84V	13.38V-13.68V	20.07V-20.52V	26.76V to 27.36V

TC Factor: (-2mV°F/cell) or (-4mV°C/cell)

2700 Carrier Ave., Commerce, CA 90040 | Email: customerservice@ramcarbatteries.com | Phone: (323) 726-1212

©2025 RAMCAR BATTERIES. All rights reserved. Trademark and logos are property of RAMCAR and its affiliates unless otherwise noted. Subject to revisions without notice.
RAMCAR BATTERIES is not liable for damages arising from information in or omitted from this document.