# GENERAL / UTILITY BATTERIES


## DSAM26/26R-6 MF





### MECHANICAL SPECIFICATIONS

| | |
|---|---|
| **Group Size** | 26, 26R |
| **Terminal Type** | Standard |
| **L x W x H x TH [in]** | 8.1 x 6.8 x 6.9 x 7.7 in |
| **L x W x H x TH [mm]** | 206 x 172 x 174 x 196 mm |
| **Weight [lbs / kg]** | 29.1 lbs / 13.2 kg |
| **Case Material** | Polypropylene |
| **Cover** | Polypropylene |
| **Handle** | Polypropylene |
| **Hold Down** | B01 |
| **Cell Layout** | 0, 1 |

### BATTERY DIAGRAMS





Terminal Type: Standard




POST TERMINAL DETAIL

Hold Down: B01




### ELECTRICAL SPECIFICATIONS

| | |
|---|---|
| **Voltage (V)** | 12V |
| **Cold Cranking Amps (CCA)** | 600 |
| **Cranking Amps (CA)** | 750 |
| **Reserve Capacity Min (RC)** | 90 min |
| **20HR Nominal Capacity (AH)** | -- |
| **Internal Resistance (mΩ)** | 3.35 mΩ |

### CHARGE DISCHARGE AND TEMPERATURE

| | |
|---|---|
| **Self-Discharge/Month 68°F (20°C)** | 2.9% |
| **Self-Discharge/Month 104°F (40°C)** | 5.6% |
| **Operating Temperature (Range)** | -4°F/-20°C to 122°F/50°C |
| **Storage Temperature (Range)** | -4°F/-20°C to 104°F/40°C |

### CHARGE VOLTAGES

| CHARGE STAGE | 12V | 24V | 36V | 48V |
|---|---|---|---|---|
| **Bulk** | 14.4-14.7V | 28.4-29.4V | 42.6-44.1V | 56.8-58.8V |
| **Absorption** | 14.2-14.7V | 28.4-29.4V | 42.6-44.1V | 56.8-58.8V |
| **Float** | 13.2 V-13.6V | 26.4V- 27.2V | 39.6V-40.8V | 52.8-54.4V |

**TC Factor: (-2mV°F/cell) or (-4mV°C/cell)**

2700 Carrier Ave., Commerce, CA 90040 | Email: customerservice@ramcarbatteries.com | Phone: (323) 726-1212

©2025 RAMCAR BATTERIES. All rights reserved. Trademark and logos are property of RAMCAR and its affiliates unless otherwise noted. Subject to revisions without notice.
RAMCAR BATTERIES is not liable for damages arising from information in or omitted from this document.